REPORT DOCUMENTATION PAGE OMB No. 0704-0188 Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing this collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number. PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS. 3. DATES COVERED (From - To) 1. REPORT DATE (DD-MM-YYYY) 2. REPORT TYPE Technical Papers 5a. CONTRACT NUMBER 4. TITLE AND SUBTITLE attached 5b. GRANT NUMBER 5c. PROGRAM ELEMENT NUMBER 5d. PROJECT NUMBER 6. AUTHOR(S) 1011 5e. TASK NUMBER 5f. WORK UNIT NUMBER 346204 8. PERFORMING ORGANIZATION 7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) REPORT Air Force Research Laboratory (AFMC) AFRL/PRS 5 Pollux Drive Edwards AFB CA 93524-7048 10, SPONSOR/MONITOR'S 9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) ACRONYM(S) Air Force Research Laboratory (AFMC) 11. SPONSOR/MONITOR'S AFRL/PRS NUMBER(S) 5 Pollux Drive Edwards AFB CA 93524-7048 12. DISTRIBUTION / AVAILABILITY STATEMENT Approved for public release; distribution unlimited. 13. SUPPLEMENTARY NOTES 14. ABSTRACT 20030116 052 15. SUBJECT TERMS 19a. NAME OF RESPONSIBLE 17. LIMITATION 18. NUMBER 16. SECURITY CLASSIFICATION OF: OF PAGES **PERSON** OF ABSTRACT Leilani Richardson 19b. TELEPHONE NUMBER a. REPORT b. ABSTRACT c. THIS PAGE (include area code) Α (661) 275-5015 Unclassified Unclassified Unclassified Standard Form 298 (Rev. 8-98)

Form Approved

FROM: PROI (TI) (STINFO)

13 Nov 2000

SUBJECT: Authorization for Release of Technical Information, Control Number: **AFRL-PR-ED-AB-2000-218**Mead, Franklin; Larson, C. William, "Laser-Powered Vertical Flight Experiments at the HELSTF"

37th AIAA/ASME/SAE/ASEE Joint Propulsion Conference (Statement A) (Salt Lake City, UT, 8-11 Jul 2001) (Deadline for Abstract: 08 Nov 00)

This request has been reviewed by the Fore b.) military/national critical technology, c.) end.) appropriateness for release to a foreign na Comments:	sport controls or distribution restrictions, tion, and e.) technical sensitivity and/or ed	conomic sensitivity.
Signature	Date _	
	<i>1</i> .	
Signature		
3. This request has been reviewed by the STE b.) appropriateness of distribution statement, e.) parallel review completed if required, and Comments:	c.) military/national critical technology, df.) format and completion of meeting clea	.) economic sensitivity,
Signature	Date	
4. This request has been reviewed by PR for: appropriateness of distribution statement, d.) national critical technology, and f.) data right Comments:	technical sensitivity and economic sensiti s and patentability	
	APPROVED/APPROVED AS A	AMENDED/DISAPPROVED
	PHILIP A. KESSEL Technical Advisor	Date

Propulsion Science and Advanced Concepts Division

LASER-POWERED, VERTICAL FLIGHT EXPERIMENTS AT THE HIGH ENERGY LASER SYSTEM TEST FACILITY

Franklin B. Mead, Jr. and C. William Larson Propulsion Directorate Air Force Research Laboratory Edwards AFB CA 93524

In 1996, the Air Force Research Laboratory's Propulsion Division at Edwards AFB initiated a program that had as its main objective to launch a laser-propelled vehicle into a suborbital trajectory within a period of 5 years in order to demonstrate the concept and its attractive features. The concept is a nanosatellite in which the laser propulsion engine and satellite hardware are intimately shared. The forebody aeroshell acts as an external compression surface (i.e., the airbreathing engine inlet). The afterbody has a dual function as a primary receptive optic (parabolic mirror) for the laser beam and as an external expansion surface (plug nozzle). The primary thrust structure is the centrally located annular shroud. The shroud provides air through inlets and acts as a energy absorption chamber for plasma formation in the airbreathing mode. In the rocket mode, the air inlets are closed, and the afterbody and shroud combine to form the rocket thrust chamber and plug ("aerospike-type") nozzle. The full scale vehicle has a focal diameter of one meter and a dry mass of about 1 kg. Fully fueled, this vehicle would have an initial mass of about 2 kg (i.e., a mass fraction of 0.5), and would be launched into orbit with a megawattclass infrared ground-based laser (GBL). It would be a single-stage-to-orbit (i.e., airbreathing with infinite I_{sp} to M=5 and 30 km; a laser thermal rocket with its own on-board propellant at higher altitudes and in space) using a combined-cycle pulsed detonation engine. Once in space, the Lightcraft will use its one meter diameter optical system to provide, for example, Earth surveys with from 8 to 15 cm resolution in the visible light frequencies from low Earth orbit (LEO). Such a device is simple, reliable, safe, and environmentally clean, and could have a very high all azimuth, on demand launch rate. The current launch model under consideration would launch up to 1,000 vehicles per year, each for under \$500 of electrical power. Production costs of about \$3,000 for the spacecraft appear reasonable at present.

The Lightcraft Technology Demonstration Program was planned in three phases. Phase I, Lightcraft Concept Demonstration, was to demonstrate the feasibility of the basic concept. This phase ended in December 98. Under Phase I, performance was measured with pendulum impulse and piezoelectric thrust stands, shadowgraph studies and beam propagation energy measurements to 90 m were accomplished, a pointing and tracking system was developed and demonstrated on horizontal wire-guided flights outdoors to 122 m, and outdoor vertical free-flights approaching 30 m were successfully conducted. Low Mach number wind tunnel tests were also accomplished with a 23-cm diameter model. The basic conclusion of all this work was that the feasibility and basic physics of the Lightcraft concept had been adequately demonstrated, and that a much larger, 100 kW class, laser would be required to completely accomplish Phase II.

Phase II, Lightcraft Vertical Launches to Extreme Altitudes, was initiated in January 99, and is a five-year effort designed to extend Lightcraft flights in sounding rocket trajectories to 30 km with a 100 kW CO₂ laser. The objective of the current Phase II vertical flight test program is to extend Lightcraft vertical free-flights to significantly higher altitudes in the range of 150 to 300 m using the 10 kW PLVTS laser.⁵ 1/10th-scale and ¼-scale laser-powered vehicles are being used . Currently with this size vehicle, laser flight tests are being conducted at the High Energy Laser Systems Test Facility (HELSTF), White Sands Missile Range (WSMR), New Mexico, using the currently available Pulsed Laser Vulnerability Test system (PLVTS) CO₂ electric discharge laser. This laser is a pulsed wave, closed cycle, 10 kW CO₂ laser with a pulse repetition rate of 1 to 30 pps (selectable), and a variable pulse width of 5 to 30 μs. For flight test experiments, the laser is usually operated at about 25 pps and 18 μs pulse widths.⁵ The first composite, ceramic components for the laser propelled vehicle have been fabricated, laboratory tested, and flown. Performance details will be presented comparing the composite materials with aluminum which has been used up until recently. Scaling effects as a function of focal diameter will be presented, and predictions on the performance of the full scale vehicle will be made. Details of the vehicle performance during flight test experiments will also be discussed. Video footage taken during the outdoor free flight tests will be shown during the presentation.

Phase III, Lightcraft Dual Mode Vehicle, is a two-year effort designed to launch the first laser-propelled vehicle, fully functional, into space. This phase will require the construction of a megawatt class CO₂ laser with appropriate optics to meet the power beam propagation requirements.

References

- 1. Myrabo, L.N., Messitt, D.G., & Mead, F.B., Jr., "Ground and Flight Tests of a Laser Propelled Vehicle," AIAA 98-1001, 36th Aerospace Sciences Meeting & Exhibit, Reno NV, 12-15 Jan 98.
- 2. Mead, F.B., Jr., Myrabo, L.N., & Messitt, D.G., "Flight and Ground Tests of a Laser-Boosted Vehicle," AIAA 98-3735, 34th AIAA/ASME/SAE/ASEE Joint Propulsion Conf., Cleveland OH, 13-15 Jul 98.
- 3. Messitt, D.G., Myrabo, L.N., Mead, F.B., Jr., "Laser Initiated Blast Wave for Launch Vehicle Propulsion," AIAA 2000-3848, 36th AIAA/ASME/SAE/ASEE Joint Propulsion Conf., Huntsville AL, 17-19 Jul 00.
- 4. Panetta, A.D., Negamatsu, H.T., Myrabo, L.N., Minucci, M.A.S., Mead, F.B., Jr., "Low Speed Wind Tunnel Testing of a Laser Propelled Vehicle," SAE International and AIAA 1999-01-5577, 1999 World Aviation Conf., San Francisco CA, 19-21 Oct 99.
- 5. Mead, F.B., Jr., Squires, S., Beairsto, C., & Thurston, M., "Flights of a Laser-Powered Lightcraft During Laser Beam Hand-off Experiments," AIAA 2000-3484, 36th AIAA/ASME/SAE/ASEE Joint Propulsion Conf., Huntsville AL, 16-19 Jul 00.